



FMF system

External width: 266mm
Internal width: 200mm
Length: 1000mm

Channel reference	Height (mm)		Hydraulic section (cm ²)	Ø outlet (mm)	
	a	b		Vert.	Horiz.
F200MF00R	263	212	374	200	160
F200MF10R	313	262	473	200	160
F200MF20R	363	312	571	200	160

Review: 2013-03

ULMA Architectural Solutions reserves the right to modify the specifications of any of its products without prior notice.

Information about the shown products is only indicative and is based on the existing technical features at the time of issuing.

In the event of any discrepancy in the translation of this document into different languages, the Spanish version will be used.

Latest version in www.ulmaarchitectural.com

For more details, see technical sheets and installation guide.

Description

ULMA polymer concrete linear drainage channel model F200MF.

Casted espheroidal graphite ductile iron edge with passivating and corrosion resistant effect.

Ø point bolt-locked system per lm.

Load class up to F900, EN1433 Standard.

Vertically and horizontally channel aligning tongue and groove joints.

CE Conformity Declaration and compliance with EN 1433 Standard.

External width 266 mm, internal width 200 mm and total length 1000 mm. Total external heights available between 263 mm and 363 mm. Installation possible with no slope or stepped fall.



ARCHITECTURAL SOLUTIONS



Tel.: +34 943 78 06 00
Info@ulmaarchitectural.com
ulmaarchitectural.com