



FMF system

External width: 163mm

Internal width: 100mm

Length: 1000mm

Channel reference	Height (mm)		Hydraulic section (cm ²)	Ø outlet (mm)	
	a	b		Vert.	Hortz.
F100MF000R	130	83	70	110	-
F100MF00R	190	143	126	110	110
F100MF10R	250	203	184	110	110
F100MF20R	310	263	242	110	110

Review: 2013-03

ULMA Architectural Solutions reserves the right to modify the specifications of any of its products without prior notice.

Information about the shown products is only indicative and is based on the existing technical features at the time of issuing.

In the event of any discrepancy in the translation of this document into different languages, the Spanish version will be used.

Latest version in www.ulmaarchitectural.com

For more details, see technical sheets and installation guide.

Description

ULMA polymer concrete linear drainage channel model F100MF.

Casted espheroidal graphite ductile iron edge with passivating and corrosion resistant effect.

8 point bolt-locked system per lm.

Load class up to F900, EN 1433 Standard.

Vertically and horizontally channel aligning tongue and groove joints.

CE Conformity Declaration and compliance with EN 1433 Standard.

External width 163 mm, internal width 100 mm and total length 1000 mm. Total external heights available between 130 mm and 310 mm. Installation possible with no slope or stepped fall.



ARCHITECTURAL SOLUTIONS



Tel.: +34 943 78 06 00
info@ulmaarchitectural.com
ulmaarchitectural.com