

CIRCLULAR FULL VISION REVOLVING DOOR



Exceptional transparency

Bespoke Design

Circular Full Vision revolving doors are all designed and manufactured to order, ensuring an unrivalled level of attention to detail, quality and design flexibility. Using the very best materials and featuring a distinctive glass ceiling, these doors are designed both to impress and provide an energy efficient entrance to grace any building. The principle characteristic of all Full Vision revolving doors is the impressive glass ceiling which provides exceptional transparency and allows the door to blend in with any architectural surroundings. The Circular Full Vision is available with 2, 3 or 4 door leaves and with diameters up to 3000 mm. All sizes are available in manual, semi-automatic or fully-automatic versions and can be supplied in heights in excess of 9 metres. As an option the Circular Full Vision revolvers can have a security function with swipe cards. The internal construction is formed from stainless steel for maximum durability and this can be overlaid with a variety of materials to produce an outstanding finish.

TECHNICAL DATA.

Product Reference:	CIRCULAR FULL VISION REVOLVING DOOR
Material:	Glass
Number of wings:	Two Wing Three Wing Four Wing
Operation:	Manual Semi-Automatic Fully Automatic Security mode with controlled access
Diameter:	1800mm – 3000mm. Available in 1mm increments
Internal Height:	3000mm – 9000mm+. Available in 1mm increments
Clear Opening:	720mm – 2060mm* *Dependent on door configuration and diameter
Locking:	Manual Automatic (Semi-Automatic & Fully Automatic Versions Only)

Glazing:	Singled Glazed/Double Glazed Clear Low Iron Coloured Fritted Special Glazing Options
Glass Roof Thickness:	18mm
Surface Finishes:	Stainless Steel Polyester Powder Coated Special Finishes on request
Accessories:	Night Security Screens or Night Security Wall Matting, Water Drainage Reservoir Heaters integrated into the mat well RC2, RC3, PAS24:2016 and Ballistic Options Available
Push Bars:	Vertical or Horizontal Handles are available
Safety:	Designed, Manufactured and installed to EN 16005
Power Supply:	230 V/50 Hz (Semi-Automatic & Fully Automatic Only)
Drive Unit:	Underfloor Drive Unit (Semi-Automatic & Fully Automatic Only) Pit size 1200 x 400x400mm (L x W x D)
Warranties:	Two Years or Lifetime with service contract* *Please contact Bauporte for further information
Construction:	Fixed curved drum walls will be constructed from clear curved 12mm glass in one piece over full height of the door and divided by the midstyle. No bottom glazing profiles, the glazing fits directly into the floor construction. Framework is constructed of welded through stainless steel sections for added durability and strength. This can be over clad with the chosen surface finish. Glass roof constructed from clear toughened and float glass laminated together, the edge is poly polished. Rotating door element part framed with no centre post, the glazing is 12mm and fully bonded together. The door leaves are provided with single or double brushes on all edges.

www.bauporte.com

BV Bauporte Design Entrances
Zandsteen 14, 2132 MR Hoofddorp,
Netherlands, Postbus 558,
2130 AN Hoofddorp
Tel: +31 (0)85 066 1203
Sales: sales@bauporte.com

Bauporte Doors UK Ltd
Office 212, Dowgate House,
14-16 Dowgate Hill, London
EC4R 2SU
Tel: +44 (0)20 3411 5023
Sales: sales@bauporte.com

Making an entrance 