



Air cooled screw  
chiller, standard  
efficiency, low  
sound

EWAD-E-SL

**R-134a**



Screw compressor

- › One refrigerant circuit with single screw compressor
- › Compact design with brazed plate heat exchanger

- › Large operation range (ambient temperature down to  $-18^{\circ}\text{C}$ )
- › Water supply down to  $-15^{\circ}\text{C}$

# EWAD-E-SL



Cooling only				EWAD-E-SL	100	120	130	160	180	210	250	300	350	400
Cooling capacity	Nom.		kW		97.6	116	134	157	177	208	248	295	344	397
Power input	Cooling	Nom.	kW		39.2	48.3	53.4	60.8	68.3	72.8	85.4	111	135	152
Capacity control	Method				Stepless									
	Minimum capacity		%		25.0									
EER					2.49	2.39	2.50	2.57	2.59	2.86	2.90	2.65	2.55	2.62
ESEER					2.92	2.88	2.76	2.91	2.98	3.22	3.44	3.31	3.24	3.35
IPLV					3.32	3.21	3.30	3.46	3.28	3.48	3.86	3.75	3.63	3.76
Dimensions	Unit	Height	mm		2,273						2,223			
		Width	mm		1,292						2,236			
		Depth	mm		2,165		3,065		3,965		3,070			
Weight	Unit		kg		1,784		1,961		2,186		3,029			
	Operation weight		kg		1,799		1,981		2,216		3,073			
Water heat exchanger	Type				Plate heat exchanger									
	Water flow rate	Cooling	Nom.	l/s	4.7	5.5	6.4	7.5	8.4	10.0	11.9	14.1	16.5	19.0
	Water pressure drop	Cooling	Nom.	kPa	23		22		21		45		44	
	Water volume		l	12	15	17	20	24	30	25	30	36	44	
Air heat exchanger	Type				High efficiency fin and tube type with integral subcooler									
Compressor	Type				Single screw compressor					Asymmetric single screw compressor				
	Quantity				1									
Fan	Type				Direct propeller									
	Quantity				2		3		4		6			
	Air flow rate	Nom.	l/s	8,373	8,144	12,560	12,216	16,747	16,288	25,120		24,432		
	Speed		rpm	700										
Sound power level	Cooling	Nom.	dB(A)	89		90				92		93		
Sound pressure level	Cooling	Nom.	dB(A)			71				73		74		
Operation range	Air side	Cooling	Min.-Max.	°CDB	-18~-48									
	Water side	Cooling	Min.-Max.	°CDB	-15~-15									
Refrigerant	Type / GWP				R-134a / 1,430									
	Circuits	Quantity			1									
Refrigerant charge	Per circuit		kg	18.0	21.0	23.0	28.0	34.0	39.0	46.0	56.0	74.0		
			TCO <sub>Eq</sub>	25.7	30.0	32.9	40.0	48.6	55.8	65.8	80.1	105.8		
Piping connections	Evaporator water inlet/outlet (OD)				3"									
Unit	Starting current	Max	A	151		195		288		330		410		
	Running current	Cooling	Nom.	A	67	83	92	103	116	122	144	184	223	249
			Max	A	83	100	115	128	151	158	189	234	276	290
Power supply	Phase/Frequency/Voltage		Hz/V	3~/50/400										

Cooling: entering evaporator water temp. 12°C; leaving evaporator water temp. 7°C; ambient air temp. 35°C; full load operation.

Equipment contains fluorinated greenhouse gases. Actual refrigerant charge depends on the final unit construction, details can be found on the unit labels.

For more information email [info@daikinapplied.uk](mailto:info@daikinapplied.uk) or visit [www.daikinapplied.uk](http://www.daikinapplied.uk)

**London Sales Office**  
69 Questor Estate  
Pearsons Way  
Dartford, Kent  
DA1 1JN  
01322 424950

**Head Office**  
Bassington Industrial Estate  
Cramlington, Northumberland  
NE23 8AF  
01670 566159



Daikin Europe N.V. participates in the Eurovent Certification programme for Liquid Chilling Packages (LCP), Air handling units (AHU), Fan coil units (FCU) and variable refrigerant flow systems (VRF) Check ongoing validity of certificate online: [www.eurovent-certification.com](http://www.eurovent-certification.com) or using: [www.certiflash.com](http://www.certiflash.com)

The present publication is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this publication to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this publication. All content is copyrighted by Daikin Europe N.V. Printed on non-chlorinated paper.

