

Air cooled  
multi-scroll chiller,  
high efficiency,  
reduced sound

EWAQ-G-XR



Scroll compressor

- › Single refrigerant circuit (2 scroll compressors) with single evaporator
- › Compact design to allow easy indoor installation or retrofit operations
- › Micro channel heat exchanger technology reduces the amount of refrigerant used in the system, lowering environmental impact
- › Partial and total heat recovery option available
- › Stainless steel plate heat exchanger

# EWAQ-G-XR



Cooling only				EWAQ-G-XR	080	090	105	115	130	150
Cooling capacity	Nom.		kW		76.0 (1)	86.0 (1)	100 (1)	110 (1)	125 (1)	141 (1)
Power input	Cooling	Nom.	kW		26.4 (1)	29.9 (1)	34.7 (1)	39.0 (1)	43.3 (1)	49.8 (1)
Capacity control	Method				Step					
	Minimum capacity		%		50	44	50	44	50	43
EER					2.88 (1)		2.89 (1)	2.83 (1)	2.88 (1)	2.83 (1)
ESEER					4.18	4.29	4.27	4.31	4.21	4.33
IPLV					4.85	4.99	4.93	4.99	4.89	5.03
Dimensions	Unit	Height	mm		1,800			1,820		
		Width	mm		1,195					
		Depth	mm		2,680	3,200		3,800		
Weight	Unit		kg		764	880	1,021	1,050	1,116	1,153
	Operation weight		kg		774	890	1,037	1,065	1,132	1,174
Water heat exchanger	Type				Brazen plate					
	Water flow rate	Cooling	Nom.	l/s	3.6	4.1	4.8	5.3	6.0	6.7
	Water pressure drop	Cooling	Nom.	kPa	23.3	29.6	18.4	17.8	23.0	18.4
	Water volume		l		5.58	4.86		5.60		8.10
Air heat exchanger	Type				Microchannel					
Compressor	Type				Scroll compressor					
	Quantity				2					
Fan	Type				Direct propeller					
	Quantity				6		8		10	
	Air flow rate	Nom.	l/s		6,787	7,356	9,023		11,309	
	Speed		rpm		1,108					
Sound power level	Cooling	Nom.	dB(A)		80	82	84	86		
Sound pressure level	Cooling	Nom.	dB(A)		62	65	66	68	67	
Operation range	Air side	Cooling	Min.-Max.	°CDB	-10~45					
	Water side	Cooling	Min.-Max.	°CDB	-10~15					
Refrigerant	Type/GWP				R-410A/2,0875					
	Circuits	Quantity			1					
Refrigerant charge	Per circuit		kg		8.0		10.0		12.0	
			TCO <sub>2</sub> eq		16.7		20.9		25.1	
Piping connections	Evaporator water inlet/outlet (OD)				2" 1/2					
Unit	Starting current	Max	A		209	260	267	314	324	362
	Running current	Cooling	Nom.	A	54	58	63	71	78	90
		Max	A		65	71	78	85	95	109
Power supply	Phase/Frequency/Voltage			Hz/V	3~/50/400					

(1) Cooling: entering evaporator water temp. 12°C; leaving evaporator water temp. 7°C; ambient air temp. 35°C; full load operation. | Equipment contains fluorinated greenhouse gases. Actual refrigerant charge depends on the final unit construction, details can be found on the unit labels.

For more information email [info@daikinapplied.uk](mailto:info@daikinapplied.uk) or visit [www.daikinapplied.uk](http://www.daikinapplied.uk)

**London Sales Office**  
69 Questor Estate  
Pearsons Way  
Dartford, Kent  
DA1 1JN  
01322 424950

**Head Office**  
Bassington Industrial Estate  
Cramlington, Northumberland  
NE23 8AF  
01670 566159



Daikin Europe N.V. participates in the Eurovent Certification programme for Liquid Chilling Packages (LCP), Air handling units (AHU), Fan coil units (FCU) and variable refrigerant flow systems (VRF) Check ongoing validity of certificate online: [www.eurovent-certification.com](http://www.eurovent-certification.com) or using: [www.certiflash.com](http://www.certiflash.com)

The present publication is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this publication to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this publication. All content is copyrighted by Daikin Europe N.V. Printed on non-chlorinated paper.

