



Air cooled multi-scroll heat pump, high efficiency, reduced sound

EWYQ-G-XR



Scroll compressor

- › Single refrigerant circuit (2 scroll compressors) with single evaporator
- › Compact design to allow easy indoor installation or retrofit operations
- › Partial and total heat recovery option available
- › Stainless steel plate heat exchanger

# EWYQ-G-XR



Heating & Cooling				EWYQ-G-XR	075	085	100	110	120	140	160	
Cooling capacity	Nom.			kW	75.2 (1)	84.5 (1)	95.0 (1)	111 (1)	120 (1)	139 (1)	155 (1)	
Heating capacity	Nom.			kW	82.2 (2)	91.2 (2)	110 (2)	127 (2)	138 (2)	156 (2)	170 (2)	
Power input	Cooling	Nom.		kW	27.7 (1)	32.7 (1)	38.6 (1)	41.5 (1)	47.4 (1)	52.8 (1)	61.5 (1)	
	Heating	Nom.		kW	26 (2)	29 (2)	34 (2)	39 (2)	43 (2)	50 (2)	54 (2)	
Capacity control	Method			Step								
	Minimum capacity			%	50	44	50	44	50	43	50	
EER					2.71 (1)	2.59 (1)	2.46 (1)	2.68 (1)	2.52 (1)	2.64 (1)	2.51 (1)	
ESEER					3.85	3.90	3.79	3.92	3.76	3.86	3.79	
COP					3.14 (2)	3.12 (2)	3.24 (2)	3.25 (2)	3.20 (2)	3.11 (2)	3.13 (2)	
SCOP					3.25	3.20	3.46	3.42	3.39	3.33	3.35	
IPLV					4.35	4.41	4.29	4.42	4.27	4.40	4.35	
Dimensions	Unit	Height	mm	1,800								
		Width	mm	1,195								
		Depth	mm	2,826		3,426		4,026				
Weight	Unit	Operation weight		kg	880	942	1,107	1,213	1,243	1,363	1,424	
				kg	888	951	1,118	1,224	1,254	1,374	1,441	
Water heat exchanger	Type			Brazed plate								
	Water flow rate	Cooling	Nom.	l/s	3.6	4.0	4.5	5.3	5.7	6.7	7.4	
		Heating	Nom.	l/s	4.0	4.4	5.3	6.1	6.7	7.5	8.2	
	Water pressure drop	Cooling	Nom.	kPa	7.90	7.70	7.60	10.5	12.1	16.4	17.5	
		Heating	Nom.	kPa	9.50	9.10	11.2	14.4	17.2	21.7	22.5	
Water volume				l	8.10	9.40	10.8			16.7		
Air heat exchanger	Type			High efficiency fin and tube type with integral subcooler								
Compressor	Type			Scroll compressor								
	Quantity			2								
Fan	Type			Direct propeller								
	Air flow rate	Nom.		l/s	7,859		7,101	9,468		11,835		
	Speed				rpm	1,108						
Sound power level	Cooling	Nom.		dB(A)	80	82	84	86				
Sound pressure level	Cooling	Nom.		dB(A)	62	65	66	68		67		
Operation range	Air side	Cooling	Min.~Max.	°CDB	-10~-45							
		Heating	Min.~Max.	°CDB	-17~-20							
	Water side	Cooling	Min.~Max.	°CDB	-10~-15							
		Heating	Min.~Max.	°CDB	25~50							
Refrigerant	Type/GWP			R-410A/2,087.5								
	Circuits	Quantity		1								
Refrigerant charge	Per circuit			kg	1.00							
				TCO <sub>2eq</sub>	31.3		37.6	48.0		62.6		
Refrigerant circuit	Charge			kg	15		18	15				
Piping connections	Evaporator water inlet/outlet (OD)			2" 1/2								
Unit	Starting current	Max		A	210	261	267	316	323.0	363	377	
	Running current	Cooling	Nom.	A	54	60	65	71	80	90	103	
		Max		A	66	72	78	87	95	111	125	
Power supply	Phase/Frequency/Voltage			Hz/V	3~/50/400							

(1) Cooling: entering evaporator water temp. 12°C; leaving evaporator water temp. 7°C; ambient air temp. 35°C; full load operation. (2) Heating capacity, unit power input and COP are based on the following conditions: ambient 7°C; condenser 40.0/45.0°C, unit at full load operation | Equipment contains fluorinated greenhouse gases. Actual refrigerant charge depends on the final unit construction, details can be found on the unit labels.

For more information email [info@daikinapplied.uk](mailto:info@daikinapplied.uk) or visit [www.daikinapplied.uk](http://www.daikinapplied.uk)

**London Sales Office**  
69 Questor Estate  
Pearsons Way  
Dartford, Kent  
DA1 1JN  
01322 424950

**Head Office**  
Bassington Industrial Estate  
Cramlington, Northumberland  
NE23 8AF  
01670 566159



Daikin Europe N.V. participates in the Eurovent Certification programme for Liquid Chilling Packages (LCP), Air handling units (AHU), Fan coil units (FCU) and variable refrigerant flow systems (VRF) Check ongoing validity of certificate online: [www.eurovent-certification.com](http://www.eurovent-certification.com) or using: [www.certiflash.com](http://www.certiflash.com)

The present publication is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this publication to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this publication. All content is copyrighted by Daikin Europe N.V. Printed on non-chlorinated paper.

