

Polysafe™ Quattro

RRL Pendulum Test
50+
Sustainable Slip Resistance

P4
AS 4586



SAFETY FLOORING FOR
**BAREFOOT & SHOD,
WET & DRY**
ENVIRONMENTS.

NEXT GENERATION safety flooring

HSE Compliant
50+
Pendulum Wet Test

Sustainable Slip Resistance
throughout product's guaranteed life



✓
HARD
WEARING
& EASY TO
MAINTAIN

✓
PUR
Reinforcement

✓
COMMERCIAL
&
RESIDENTIAL

✓
ENHANCED
SLIP RESISTANCE
50+

Designed for **HIGH RISK** environments

Polysafe Quattro has been specifically designed to provide a high degree of slip resistance whether wearing footwear or being barefoot in continually wet areas where additional contaminants such as shampoo and shower gels may be present.

The choice of floor covering in healthcare, aged care and specialist care environments can have a significant impact on the health and well-being of residents and staff. Quattro has been designed to enhance interiors, offering a practical solution where people can feel comfortable and safe. Quattro can also make a difference in education and leisure environments, where changing rooms, wet rooms, spas and pool sides require a high degree of slip resistance.

Quattro has been engineered to achieve a pendulum wet test result of 50+ (Slider 96), most importantly this performance is sustainable and assured throughout the product's guaranteed life.



Education



Adapted Living



Healthcare



Social Housing



Leisure



SECURITY & COMFORT



Choosing the right flooring is key in promoting a more positive and inclusive environment to those living with dementia.

Designs that promote harmony and wellbeing through the creation of a sense of calm are important to resident comfort and welfare. Generating this harmonious feel is equally important whether in a residential care setting or within a person's home to support independent living. With this in mind, the Polysafe Quattro colour palette has been carefully developed.

A surface, without studs, offers superior comfort underfoot whilst maintaining high performance and safety. Residents and their carers can have confidence that their floor covering provides sustainable wet slip resistance offering protection against slips, trips and falls.

- ✓ Enhanced comfort underfoot
- ✓ Designed for residential care settings
- ✓ Safety assured
- ✓ Easy to maintain



WARM
NEUTRALS



FRESH
BLUES



SOOTHING
GREYS

THE COLLECTION


The Quattro collection draws from the calm beauty within natural environments, evoking memories of a revitalising coastal scene. The collection features warm neutrals reminiscent of sandy dunes, fresh blue shades reflecting gentle ocean waves and soothing grey tones inspired by rocky coastlines. These hues work in perfect harmony to create an ambiance of tranquillity and calmness.




Chalk Dune 5766
NCS S 1502-Y50R
LRV 60 w/r 5766



Lunar Shell 5772 ▲
NCS S 1502-Y
LRV 64 w/r 5772




Barley Cove 5761 ▲
NCS S 3005-Y50R
LRV 47 w/r 5212




Truffle Shore 5762 ▲
NCS S 5005-Y50R
LRV 24 w/r 5762



Sea Spray 5763 ▲
NCS S 3000-N
LRV 49 w/r 5202



Sea Mist 5768
NCS S 2010-B
LRV 46 w/r 5205



Calm Azure 5770
NCS S 2030-R90B
LRV 31 w/r 5206




Deep Lagoon 5771
NCS S 6010-R90B
LRV 12 w/r 5207




Cool Pebble 5767
NCS S 3000-N
LRV 46 w/r 2090



Slate Haze 5773
NCS S 5000-N
LRV 26 w/r 5764



Coastal Flint 5764 ▲
NCS S 4500-N
LRV 26 w/r 5764



Granite Sky 5765 ▲
NCS S 7502-B
LRV 10 w/r 4490

▲ These colours contain a tonal chipped decoration






CHALK DUNE


5766

w/rt 5766
NCS S 1502-Y50R
LRV: 60

Quattro is the ultimate durable choice for locker rooms and changing areas where slippery conditions caused by humidity, soap and even soil or dirt are often present.







"Over 2000 injuries a year to employees in healthcare, are attributed to slips and trips"

HSE: UK Health & Safety Executive



SEA MIST

5768

w/r: 5205
NCS S 2010-B
LRV: 46





CALM AZURE

5770

w/r: 5206
NCS S 2030-R90B
LRV: 31








**COMMERCIAL
& RESIDENTIAL
AREAS**

Quattro is the ideal solution for adapted bathrooms in care homes and residential settings.


COOL PEBBLE

5767

w/r: 2090
NCS S 3000-N
LRV: 46




Providing a high level of slip resistance in Spa and Salon environments is essential, as spills and splashes are inevitable.



COASTAL FLINT

5764

w/r: 5764
NCS S 4500-N
LRV: 26



GRANITE SKY

5765

w/r: 4490
NCS S 7502-B
LRV: 10



RECOMMENDED FINISHES



To achieve a perfect finish, it is advisable from the outset of any project to consider appropriate drainage and floor to wall detailing.

+ Watertight floor to wall finish



In continuously wet areas the appropriate floor to wall finish is equally as important as choosing the correct floor. To ensure that a watertight joint is achieved we recommend that Quattro is site-coved to the wall.

Cove formers [1] & capping strips [2] give a neat finish to the installation and ensure a continuous sealed surface.



- 
 Hygienic
- 
 Watertight
- 
 Durable
- 
 Easy to clean

+ For more information on capping or coving designs and sizes please contact us.

+ Wall Cladding




The perfect partner for Quattro

Our vinyl wall and ceiling cladding featuring a protective polyurethane surface treatment is the ideal choice for wet and hygiene critical areas.

Polyclad Pro & Plus are available in a number of subtle colours, offering an impervious floor to wall surface.

+ Drainage Systems



Only drains that have been specifically designed for use with sheet vinyl flooring should be considered in wet areas. These drains have clamping rings which prevent the ingress of water to provide a watertight finish.

The vinyl can easily be clamped between the drain's grate and built-in set to ensure a complete watertight installation.




ROUND DRAINS


+ For more information on suitable drainage systems please contact us.

PRODUCT TESTING


As the potential for slips is higher in wet environments, it is important to choose a HSE compliant flooring solution that offers sustainable slip resistance for the product's lifetime.



PENDULUM TEST



RAMP TEST



50,000 CYCLES TEST

50+ (Slider 96)
Sustainable Slip Resistance

P4
AS 4586

Quattro achieves a test value (PTV) of **50+** (Slider 96), ensuring a low slip potential.

In Australia this result means that Quattro is **P4** rated.

DIN 51130 & AS 4586

R11

DIN 51097 & AS 4586

CLASS B
AS 4586

EN 13845

The European safety flooring standard

Conformance to the 50,000 cycles abrasion test demonstrates that the performance particles within a safety floor are durable, offering longevity and sustainable performance for the guaranteed life of the product.






PUR

TECHNOLOGY

- ✓ Easy clean
- ✓ Maintain cost savings
- ✓ Optimum appearance retention
- ✓ Resistance to staining & chemicals



TECHNICAL SPECIFICATION

	Gauge	ISO 24346 (EN 428)	2.0mm
	Roll Size	ISO 24341 (EN 426)	2m x 20m = 40m ²
	Total Weight	ISO 23997 (EN 430)	2700g/m ²
	General Performance	EN 13845 ASTM F1303	Conforms Conforms
	Use Area	ISO 10874 (EN 685)	  
	Enhanced Slip Resistance	EN 13845 AS 4586 Appendix A AS 4586 Appendix C AS 4586 Appendix D DIN 51097/DIN EN 16165 Ann. A DIN 51130/DIN EN 16165 Ann. B RRL Pendulum Test Surface Roughness ASTM D2047	ESb & ESf P4 Class B R11 Class B R11 ≥50 (wet test - 4S Rubber/Slider 96) Rz ≥20µm SCOF ≥0.8
The wet slip resistance across all Polysafe products is sustainable throughout the guaranteed life of the product, with strict adherence to HSE Guidelines. For further clarification regarding slip resistance, consult Polyflor.			
	Abrasion Resistance	EN 13845	50,000 cycles
	Reaction to Fire	EN 13501-1 ASTM E648 Australian BCA Spec C1.10-3 AS ISO 9239-1 CAN/ULC S102.2	Class Bfl-S1 Class 1 Complies >8.0kW/m ² FSV < 300; SDV < 500
	Static Electrical Propensity	EN 1815	≤2kV Classified as 'antistatic'
	Water Tightness	EN 13553	Annex A
	VOC Emissions	Indoor Air Comfort GOLD AgBB/ABG FloorScore Finnish M1 Classification	Eurofins certified product Pass Certified Certified
	Resistance to Chemicals	ISO 26987 (EN 423)	Good chemical resistance
	Bacterial Resistance	ISO 846 Part C	Does not favour growth
Environmentally Preferable Flooring - Polysafe Quattro PUR achieves BRE Global A+ rating (ENP 472) in the Green Guide to Specification in use areas such as education and healthcare and is GreenTag LCA Rate certified with GreenRate level A - Gold Plus. Generic EN 15804 Environmental Product Declaration (EPD) available on request. It is 100% recyclable and contains recycled material. Recyclable via the Recofloor scheme. Visit www.polyflor.com/sustainability			
Polysafe PUR - Polysafe Quattro PUR features a high quality, cross-linked polyurethane reinforcement, UV cured to provide superior cleaning benefits, life cycle maintenance savings and optimum appearance retention. As with all Polysafe products, Polysafe Quattro PUR should not have a polish applied.			
	Hygiene	All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection.	
		Polysafe safety flooring ranges have good resistance to dilute acids and alkalis, are compatible for use with the most commonly used alco-based hand gels and are suitable for steam cleaning on a periodic basis. Chemical resistance charts available on request. For information regarding handling and installation, adhesives, maintenance, applications, chemical resistance and product warranty, consult Polyflor Customer Technical Services on +44 (0)161 767 1912 , or email tech@polyflor.com	
The data presented is correct at the time of printing. For latest information, please visit our website polyflor.com . This product contains a blend of quartz particles in various colours within the vinyl to impart the required sustainable slip resistance. Decoration and shade may vary slightly from the samples shown.			



For more information regarding our recommended safety flooring finishes or product testing please contact Customer Technical Services Department on **+44 (0)161 767 1912** or email tech@polyflor.com. Alternatively please visit polyflor.com/safety



BS EN 14041



EN 14041

FREE
SAMPLES

+44 (0)161 767 2551
polyflor.com

Polysafe™

POLYFLOR™ INTERNATIONAL

Australia

Polyflor Australia
Tel: 1800 777 425
E-mail: sales@polyflor.com.au

Canada

Polyflor Canada Inc.
Tel: +1 905 364 3000
E-mail: sales@polyflor.ca

China

Polyflor Hong Kong O/B Polyflor Ltd.
Tel: +(852) 2865 0101
E-mail: info@polyflor.com.hk

Colombia

Polyflor Ltd. (LATAM Office)
Tel: +57 (601) 7431965
E-mail: info@polyflor.com

France

James Halstead France SAS
Tel: +33 (0)8 20 20 32 11
E-mail: info@jhfrance.fr

Germany

objectflor Art und Design Belags GmbH
Tel: +49 (0) 2236 966 330
E-mail: info@objectflor.de

India

Polyflor India Pvt Ltd.
Tel: +91 22 4023 2485
E-mail: info@polyflor.co.in

Ireland

Polyflor Ireland
Tel: +353 (1) 864 9304
E-mail: salesireland@polyflor.com

Malaysia

Polyflor Martex
Tel: 1300 80 7788
E-mail: sales@polyflor.com.my

Middle East

Polyflor FZE
Tel: +971 50 406 8114
E-mail: aelwakil@polyflorfze.ae

New Zealand

Polyflor New Zealand Ltd.
Tel: 0800 765 935 Tel: +64 9 269 1111
E-mail: sales@polyflor.co.nz

Norway

Polyflor Nordic
Tel: +47 23 00 84 00
E-mail: firmapost@polyflor.no

Poland

Pollflor Sp. Z.o.o
Tel: +48 (0) 61 820 3155
E-mail: polyflor@pollflor.com.pl

South Africa

Poly Sales Africa (Pty.) Ltd.
Tel: +27 (0) 11 609 3500
E-mail: info@polyflor.co.za

Spain

Polyflor Ltd.
Tel: +34 619 949 054
E-mail: info@polyflor.com

Sweden

FalckDesign AB
Tel: +46 (0) 300 15820
E-mail: info@falckdesign.com

POLYFLOR™ UK

Polyflor Ltd. PO Box 3, Radcliffe New Road,
Whitefield, Manchester, M45 7NR

UK Sales Direct: +44 (0) 161 767 1122
UK Samples Direct: +44 (0) 161 767 2551
Export Sales Direct: +44 (0) 161 767 1913
Technical Support: +44 (0) 161 767 1912
E-mail: info@polyflor.com

polyflor.com/safety

