

Jaymart

**Plaza
Vinyl
Flooring**

Plaza Safe-T-Decor

Plaza Safe-T-Decor is an extensive range of heavy-duty, textured, slip-resistant vinyl floorings in traditional, modern and hi-tech finishes that is ideally suited to heavy traffic areas such as schools and colleges, museums and art galleries, public buildings and leisure facilities, buses, coaches, trains and maritime areas, lifts and corridors, etc.

- Very high anti-slip rating (R12)
- Polyurethane reinforced for strength
- Homogeneous construction for durability
- No wax, no polish maintenance
- IMO tested for maritime usage

5 surface finishes
Roll size 15m x 2m
2.2mm thick

When required the joints between runs of Plaza Safe-T-Decor can be cold welded. Please note that due to the manufacturing process of this type of material, stud or pattern alignment cannot be guaranteed between runs of material.

Plaza Safe-T-Floor

Plaza Safe-T-Floor is a new and exciting range of contemporary, slip-resistant, heavy-traffic, vinyl flooring with traditional anti-slip properties designed for use in typically wet areas in hospitals, nursing homes, schools, colleges and commercial kitchens, and consequently performs exceptionally well on buses, coaches & trains.

- High Anti-Slip rating (R10)
- Silicon Carbide granules for hardness
- Polyurethane reinforced for strength
- Homogeneous construction for durability
- No wax, no polish maintenance
- Extensive colour range
- IMO tested for maritime usage
- Fungi and bacteria resistance

3 contemporary surface finishes
Roll size 15m x 2m
2.0mm thick

Matching welding rods are available for hot welding in all colours. Cold welding is usually suggested for Round Stud design. Please note that due to the manufacturing process stud alignment cannot be guaranteed between runs of material on the round stud design.

Plaza Safe-T-Wood

Plaza Safe-T-Wood is a new and exclusive range of vinyl sheet flooring, manufactured using state-of-the-art production techniques to give an exceptionally realistic wood effect - not just in appearance, but also in texture. The convincing wood effect means that Plaza Safe-T-Wood is perfectly 'at home' at home, but the tough polyurethane reinforced wear layer also makes it perfect for retail environments, museums and art galleries, offices and public buildings, hotels and restaurants, schools and colleges, etc.

- Wear layer polyurethane reinforced for strength
- No wax, no polish maintenance
- IMO tested for Maritime usage
- 0.5mm wear layer


7 realistic wood finishes
Roll size 15m x 2m
2.0mm thick

Matching welding rods are available in all colours for hot welding. Alternatively cold welding techniques can be used if required.

Diamond



Large Coin





Dark Grey



Silver



Small Coin



Dark Grey



Silver





**4 Bar
Chequerplate**



**Texture
Round Stud**





Chip - Lightly textured surface
with terrazzo colour chippings



Smooth
Lightly textured surface with speckled chippings



Round Stud
Round studded
textured surface
with speckled
chippings





Plaza Safe-T-Decor



Plaza Safe-T-Floor



Plaza Safe-T-Wood

Technical Data

Technical Data for Plaza Safe-T-Floor, Plaza Safe-T-Wood and Plaza Safe-T-Decor is identical apart from where indicated.

Plaza Safe-T-Decor	Homogeneous vinyl safety flooring
Plaza Safe-T-Floor	Homogeneous vinyl safety flooring incorporating Silicon Carbide granules
Plaza Safe-T-Wood	Heterogeneous wood effect vinyl flooring

Commercial 34

Industrial 43



General Performance EN 685 : 1996
EN 649 : 1997

Property	Standard	Plaza Safe-T-Decor	Plaza Safe-T-Floor	Plaza Safe-T-Wood
Thickness	EN 428	Plaza Safe-T-Decor 2.2mm	Plaza Safe-T-Floor 2.0mm	Plaza Safe-T-Wood 2.0mm
Sheet	EN 426	2m x 15m = 30m ²		
Weight	EN 430	Plaza Safe-T-Decor 4.00kg/m ²	Plaza Safe-T-Floor 3.50kg/m ²	Plaza Safe-T-Wood 3.50kg/m ²
Reaction To Fire	EN 13501-1 EN ISO 9239-1 EN ISO 11925-2 ASTM E648-06	Class Bfl-S1 ≥ 8kw/m ² Pass Type 1		
Flexibility	EN 435 ASTM F137	< 20mm Pass		
Slip Resistance	EN 13893 DIN 51130	Plaza Safe-T-Decor Class DS R12	Plaza Safe-T-Floor Class DS R10	Plaza Safe-T-Wood Class DS R9
Abrasion Resistance	EN 660-2 ASTM D3384	Plaza Safe-T-Decor Wear Group P Pass	Plaza Safe-T-Floor Wear Group P Pass	Plaza Safe-T-Wood Wear Group T
Residual Indentation	EN 433 ASTM F970 ASTM F1914	Plaza Safe-T-Decor < 0.1mm Static load 800 psi N/A	Plaza Safe-T-Floor < 0.1mm Static load 800 psi N/A	Plaza Safe-T-Wood < 0.1mm Pass Pass
Castor Chair	EN 425	Continuous Use		
Light Fastness	EN 20105:B02 ASTM F1515	Plaza Safe-T-Decor > Blue Wool Standard 6 N/A	Plaza Safe-T-Floor > Blue Wool Standard 6 N/A	Plaza Safe-T-Wood > Blue Wool Standard 6 Pass
Wear Layer Thickness	EN 429 ASTM F410	Plaza Safe-T-Decor 2.2m N/A	Plaza Safe-T-Floor 2.0mm N/A	Plaza Safe-T-Wood 0.5mm Pass
Electrical Behaviour (body voltage)	EN 1815	< 2.0 kV		
Dimensional Stability	EN 434	< 0.4mm		
Stain and Chemical Resistance	EN 423 ASTM F925	Plaza Safe-T-Decor Good Resistance N/A	Plaza Safe-T-Floor Good Resistance N/A	Plaza Safe-T-Wood Good Resistance Pass
Thermal Resistance	ISO 8302 (EN 12664) ASTM 1514	< 0.00752 m ² K/W Pass	Plaza Safe-T-Wood ONLY	
Smoke Density	ASTM E 662-05	< 450		
Fungi and Bacteria Resistance		Does not favour growth		
Clean Rooms	ASTM F51/68	Class A - non-shedding Suitable for use in following classes of clean room: ISO 1466-11999 Class 4		
Maritime Usage	IMO RES A 653 (16) IMO MSC 61 (67) US Coast Guard Approved Marine Equipment Directive	Annex 1 part 2 (Smoke & Toxicity) Part 5 (Spread of Flame) and Annex 2 (Surface Flammability/Heat Release)		





Jaymart

**Jaymart Rubber &
Plastics Limited**

**Roman Way, Crusader
Park,**

Warminster

BA12 8SP

Tel 01985 218994

**Email:
sales@jaymart.co.uk**

www.jaymart.co.uk