

# SAFETRACK® HW PATCH PACK

Anti-Skid Patch Repair

## Description

Stirling Lloyd's, now GCP Applied Technologies SAFETRACK® HW is a liquid applied system designed for localised areas requiring anti-skid. Based on GCP, previously Stirling Lloyd's, unique ESSELAC® advanced resin technology and extensive experience in the development of high performance specialist surfacing, it is suitable for the rapid, reinstatement of damaged or compromised road surfaces or for the reinstatement of anti-skid surfacing following maintenance work. SAFETRACK® HW is a Type 1 certified BBA/HAPAS High Friction Surfacing System that also conforms to Clause 924 of the UK Specification for Highway Works (March 1998) for Resin Based High Skid Resistant Surface Treatments.

The PATCH PACK contains all the necessary materials and equipment to successfully and easily apply the material.

## Advantages

- Offers first time reinstatement
- Quick, simple and economical to apply
- Cold applied – no hot trades
- Can be applied as soon as fresh asphalt cools to ambient temperature
- Excellent adhesion to a variety of substrates
- Longer service life – less maintenance
- Fast return to service
- Self-contained application kit

## Technical Data

SAFETRACK® HW is CE Marked under EN1504-2 for which a Declaration of Performance is available on request.

| PROPERTY                                   | VALUE       |
|--|-------------|
| Application Temperature Range <sup>1</sup> | 0°C to 30°C |
| Typical Working Life<br>20°C               | 7 minutes   |
| 0°C  | 10 minutes  |
| Typical Cure / Drive On Time<br>20°C       | 30 minutes  |
| 0°C  | 55 minutes  |

## Surface Preparation

All substrates must be clean, dry and structurally sound. Dry with a gas burner if required.

## Application

Each patch pack contains easy to follow step by step pictorial Application Guidelines.

## Coverage

Typically 1 - 2m<sup>2</sup> per patch pack, depending on surface texture.

Application onto Stone Mastic Asphalt (SMA) and other types of porous asphalt may lead to an increase in the required coverage rate.

## Aggregates & Colour

1-3mm bauxite is included in the pack.

Standard colours are Buff, Green, Grey & Red.

## Packaging & Storage

SAFETRACK® HW Patch Pack is supplied in a single container with all the necessary materials and equipment to apply the product.

All components should be stored in cool, dry, protected conditions, out of direct sunlight and in accordance with the relevant site Health & Safety regulations. Storage temperature must not exceed 25°C. Do not store near naked flames or foodstuffs.

Stored in unopened containers, under the correct conditions, the components have a minimum shelf life of twelve months. If your product is more than twelve months old contact Technical Service before use.

## Limitations

Do not apply SAFETRACK® HW on to surface dressings or Bitmac surfaces.

## Health & Safety

Please refer to our Safety Data Sheets for further information.

## General Information

SAFETRACK® HW Patch Pack is just one of a wide range of specialist highway maintenance, surfacing, waterproofing and repair materials manufactured and supplied by GCP (formerly Stirling Lloyd). If you require any further information on this or any other of our products, please contact Technical Services or visit our website [www.gcpat.com](http://www.gcpat.com).

<sup>1</sup> For temperatures outside this range, please contact Technical Service

gcpat.com | Technical Services, Manchester, UK (+44 (0) 1565 633111)

We hope the information here will be helpful. It is based on data and knowledge considered to be true and accurate, and is offered for consideration, investigation and verification by the end user, but we do not warrant the results to be obtained. Please read all statements, recommendations, and suggestions in conjunction with our conditions of sale, which apply to all goods supplied by us. No statement, recommendation, or suggestion is intended for any use that would infringe any patent, copyright, or other third party right.

SAFETRACK® and ESSELAC® are trademarks, which may be registered in the United States and/or other countries, of GCP Applied Technologies Inc. This trademark list has been compiled using available published information as of the publication date and may not accurately reflect current trademark ownership or status.

© Copyright 2018 GCP Applied Technologies Inc

All rights reserved GCP Applied Technologies Inc., 62 Whittemore Avenue, Cambridge, MA 02140 USA.  
GCP Applied Technologies (UK) Limited, 487-488 Ipswich Road, Slough, Berkshire, SL1 4EQ, UK

Last Updated: 2021-06-22



Certificate Number 15174  
ISO 9001, ISO 14001

