

Aruba hH


Aruba hH is a tough and reliable humidity resistant ceiling tile. Stable at up to 99% Relative Humidity (RH), it is ideal for high humidity areas such as changing rooms.

Key Features

- Up to 99% RH
- Available in Board edge
- Offers Class C sound absorption and good attenuation for excellent acoustic performance
- Available in Global White, giving warm and damp spaces a brighter and cooler appearance
- Ideal for high humidity areas such as changing rooms
- Excellent technical performance in humid conditions when used alongside Prelude 24 Corrosive Resistant suspended ceiling grid



Edge Detail Board



Thickness (mm) 15

Modules (mm) 600 x 600 5499M

Suspension Systems Gridline 24 Butt Cut / Joggled
Gridline 24 Corrosive Resistant
Prelude 24 Sixty²

Colour Global White

Sustainability


44






A


EN 13964 / E1



Acoustics



EN ISO 354 & EN ISO 11654



EN ISO 10848-2 & EN ISO 717-1


| | Hz α_p | | | | | | | | | |
|-------|---------------|-----------|-------|------|------|------|------|------|------|------|
| | α_w | D_{nfw} | Class | NRC | 125 | 250 | 500 | 1000 | 2000 | 4000 |
| Board | 0.60 | 34 dB | C | 0.55 | 0.35 | 0.45 | 0.60 | 0.60 | 0.60 | 0.60 |


Fire Reaction  Euroclass A2-s1, d0
EN 13501-1


Performances & Features


 85%


 99% RH












 3.6 Kg/m²







If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on **0800 371 849** or email enquiries@zentia.com

TDS 138.3.03.24